



KEYNOTES

- ① SUB-BASE OPTIONS PER ADA GUIDELINES: (1) CONCRETE - MINIMUM OF 3-4" AT A MINIMUM 2500 PSI. MUST CURE FOR 7 DAYS PRIOR TO CUSHION LAYER. MUST CURE FOR 28 DAYS IF WEAR COURSE IS TO BE APPLIED DIRECTLY TO CONCRETE SURFACE. (2) ASPHALT - MUST CURE A MINIMUM OF 14 DAYS, POWER WASHED
- ② SYNTHETIC TURF, INSTALL PER MANUFACTURER GUIDELINES
- ③ EXISTING SOLID COMPACTED DIRT
- ④ SBR CUSHION LAYER OR FOAM PAD PER JOB SPECIFICATIONS (DEPTH VARIES BY CRITICAL FALL HEIGHT)
- ⑤ DESIGNATED FALL ZONE EDGE PER JOB SPECIFICATIONS
- ⑥ TURN DOWN (45 DEGREE MAXIMUM)
- ⑦ 2" X 3" KEYWAY CUT OR FORMED INTO SUB-BASE
- ⑧ TURF NAIL BOARD SECURED TO SUB-BASE BORDER AREA. (2" X 4" COMPOSITE LUMBER IS PREFERRED) SECURE LANDSCAPE SPIKES INTO KEYWAY
- ⑨ TURF FASTENER SECURING TURF TO NAIL BOARD
- ⑩ 1.5 - 2.5 LBS/SF INFILL PER MANUFACTURER GUIDELINE TO GRADE LEVEL

ROBERTSON RECREATIONAL SERVICES
ADDRESS: 2414 W. 12TH STREET SUITE 5
TEMPE, ARIZONA 85281
PHONE: 800-858-0519
WEBSITE: WWW.TOTTURF.COM

DETAIL-15
TOTTURF SYNTHETIC WITH TURNDOWN
(CONCRETE / ASPHALT, AGGREGATE)

DATE: 09-20-2016
REVISION DATE: 12-12-2016
SCALE: N.T.S.
DRAWN BY: ATL
SIGNED/APPROVED: