



KEYNOTES

- ① SUB-BASE OPTIONS PER ADA GUIDELINES: (1) COMPACTED AGGREGATE - 4" OF 3/4" MINUS IRREGULAR STONE WITH FINES COMPACTED TO 95% IN 2" WATERED LIFTS. (2) CONCRETE - MINIMUM OF 3-4" AT A MINIMUM 2500 PSI. MUST CURE FOR 7 DAYS PRIOR TO CUSHION LAYER. MUST CURE FOR 28 DAYS IF WEAR COURSE IS TO BE APPLIED DIRECTLY TO CONCRETE SURFACE. (3) ASPHALT - MUST CURE A MINIMUM OF 14 DAYS, POWER WASHED
- ② WEAR COURSE - 1/2" INCH MINIMUM THICKNESS
- ③ EXISTING SOLID COMPACTED DIRT
- ④ SBR CUSHION LAYER PAD PER JOB SPECIFICATIONS (DEPTH VARIES BY CRITICAL FALL HEIGHT)
- ⑤ SYNTHETIC TURF, INSTALL PER MANUFACTURER GUIDELINES
- ⑥ SUB-BASE PER JOB SPECIFICATION (SBR CUSHION LAYER, COMPACTED AGGREGATE, EXISTING EARTH)
- ⑦ 4" EPOM STEP W/ TURF GLUED TO STEP
- ⑧ 1.5 - 2.5 LBS/SF INFILL PER MANUFACTURER GUIDELINE TO GRADE LEVEL

ROBERTSON RECREATIONAL SERVICES
ADDRESS: 2414 W. 12TH STREET SUITE 5
TEMPE, ARIZONA 85281
PHONE: 800-858-0519
WEBSITE: WWW.TOTTURF.COM

DETAIL-16
TOTTURF SYNTHETIC TO PIP EDGE

DATE: 09-20-2016
REVISION DATE: 12-12-2016
SCALE: N.T.S.
DRAWN BY: ATL
SIGNED/APPROVED: