



KEYNOTES

- ① SUB-BASE OPTIONS PER ADA GUIDELINES: (1) CONCRETE - MINIMUM OF 3'-4" AT A MINIMUM 2500 PSI. MUST CURE FOR 7 DAYS PRIOR TO CUSHION LAYER. MUST CURE FOR 28 DAYS IF WEAR COURSE IS TO BE APPLIED DIRECTLY TO CONCRETE SURFACE. (2) ASPHALT - MUST CURE A MINIMUM OF 14 DAYS, POWER WASHED
- ② CONCRETE WALK OR BORDER EDGE
- ③ EXISTING SOLID COMPACTED DIRT
- ④ INTERLOCKING TILES (HEIGHT VARIES BY CRITICAL FALL HEIGHT REQUIREMENTS AND PRODUCT SOLD)

ROBERTSON RECREATIONAL SERVICES
ADDRESS: 2414 W. 12TH STREET SUITE 5
TEMPE, ARIZONA 85281
PHONE: 800-858-0519
WEBSITE: WWW.TOTURF.COM

DETAIL-19
INTERLOCKING TILE OVER
CONCRETE / ASPHALT

DATE: 09-20-2016
REVISION DATE: 12-12-2016
SCALE: N.T.S.
DRAWN BY: ATL
SIGNED/APPROVED: