



KEYNOTES

- ① SUB-BASE OPTIONS PER ADA GUIDELINES: (1) CONCRETE - MINIMUM OF 3'-4" AT A MINIMUM 2500 PSI. MUST CURE FOR 7 DAYS PRIOR TO CUSHION LAYER. MUST CURE FOR 28 DAYS IF WEAR COURSE IS TO BE APPLIED DIRECTLY TO CONCRETE SURFACE. (2) ASPHALT - MUST CURE A MINIMUM OF 14 DAYS, POWER WASHED
- ② WEAR COURSE - 1/2" INCH MINIMUM THICKNESS OVER PRIMED CONCRETE / ASPHALT
- ③ 1" DEEP, 1" WIDE INSTALLATION KEYWAY

ROBERTSON RECREATIONAL SERVICES
ADDRESS: 2414 W. 12TH STREET SUITE 5
TEMPE, ARIZONA 85281
PHONE: 800-858-0619
WEBSITE: WWW.TOTURF.COM

DETAIL--2
1/2" PIP WEAR COURSE OVER CONCRETE/
ASPHALT (NO ATTENUATION)

DATE: 09-12-2016
REVISION DATE: 12-12-2016
SCALE: N.T.S.
DRAWN BY: ATL
SIGNED/APPROVED: