



**KEYNOTES**

- ① SUB-BASE OPTIONS PER ADA GUIDELINES: (1) COMPACTED AGGREGATE - 4" OF 3/4" MINUS IRREGULAR STONE WITH FINES COMPACTED TO 95% IN 2" WATERED LIFTS. (2) CONCRETE - MINIMUM OF 3-4" AT A MINIMUM 2500 PSI. MUST CURE FOR 7 DAYS PRIOR TO CUSHION LAYER. MUST CURE FOR 28 DAYS IF WEAR COURSE IS TO BE APPLIED DIRECTLY TO CONCRETE SURFACE. (3) ASPHALT - MUST CURE A MINIMUM OF 14 DAYS, POWER WASHED
- ② WEAR COURSE - 1/2" INCH MINIMUM THICKNESS
- ③ 1-1/2" 45 DEGREE EDGE BEVEL AGAINST PRIMED CONCRETE BORDER TO PREVENT SHRINKING
- ④ SBR CUSHION LAYER (DEPTH VARIES BY CRITICAL FALL HEIGHT REQUIREMENTS AND PRODUCT SOLD)
- ⑤ CONCRETE BORDER

**ROBERTSON RECREATIONAL SERVICES**  
ADDRESS: 2414 W. 12TH STREET SUITE 5  
TEMPE, ARIZONA 85281

PHONE: 800-858-0619  
WEBSITE: WWW.TOTURF.COM

**DETAIL-5**

**FLUSH MOUNT TO WALL, CURB, OR  
SIDEWALK (EXISTING CONSTRUCTION)**

DATE: 09-12-2016

REVISION DATE: 12-12-2016

SCALE: N.T.S.

DRAWN BY: ATL

SIGNED/APPROVED: