



**KEYNOTES**

- ① SUB-BASE OPTIONS PER ADA GUIDELINES: (1) COMPACTED AGGREGATE - 4" OF 3/4" MINUS IRREGULAR STONE WITH FINES COMPACTED TO 95% IN 2" WATERED LIFTS. (2) CONCRETE - MINIMUM OF 3-4" AT A MINIMUM 2500 PSI. MUST CURE FOR 7 DAYS PRIOR TO CUSHION LAYER. MUST CURE FOR 28 DAYS IF WEAR COURSE IS TO BE APPLIED DIRECTLY TO CONCRETE SURFACE. (3) ASPHALT - MUST CURE A MINIMUM OF 14 DAYS, POWER WASHED
- ② WEAR COURSE - 1/2" INCH MINIMUM THICKNESS
- ③ EXISTING SOLID COMPACTED DIRT
- ④ SBR CUSHION LAYER (DEPTH VARIES BY CRITICAL FALL HEIGHT REQUIREMENTS AND PRODUCT SOLD)
- ⑤ 1-1/2" DEEP 45 DEGREE BEVEL AGAINST PRIMED POST TO PREVENT SHRINKING
- ⑥ CONCRETE EQUIPMENT FOOTING

ROBERTSON RECREATIONAL SERVICES  
ADDRESS: 2414 W. 12TH STREET SUITE 5  
TEMPE, ARIZONA 85281  
PHONE: 800-858-0519  
WEBSITE: WWW.TOTFURF.COM

**DETAIL-6**  
POST / POLE EDGE PIP INSTALLATION

DATE: 09-13-2016  
REVISION DATE: 12-12-2016  
SCALE: N.T.S.  
DRAWN BY: ATL  
SIGNED/APPROVED: