



KEYNOTES

- ① SUB-BASE OPTIONS PER ADA GUIDELINES: (1) COMPACTED AGGREGATE - 4" OF 3/4" MINUS IRREGULAR STONE WITH FINES COMPACTED TO 95% IN 2" WATERED LIFTS. (2) CONCRETE - MINIMUM OF 3-4" AT A MINIMUM 2500 PSI. MUST CURE FOR 7 DAYS PRIOR TO CUSHION LAYER. MUST CURE FOR 28 DAYS IF WEAR COURSE IS TO BE APPLIED DIRECTLY TO CONCRETE SURFACE. (3) ASPHALT - MUST CURE A MINIMUM OF 14 DAYS, POWER WASHED
- ② WEAR COURSE - 1/2" INCH MINIMUM THICKNESS
- ③ 45 DEGREE TURN-DOWN OF WEAR COURSE AND SBR LAYER TO FULL DEPTH OF LOOSE FILL PIT AREA
- ④ SBR CUSHION LAYER (DEPTH VARIES BY CRITICAL FALL HEIGHT REQUIREMENTS AND PRODUCT SOLD)
- ⑤ CONCRETE BORDER
- ⑥ LOOSE FILL MATERIAL

ROBERTSON RECREATIONAL SERVICES
ADDRESS: 2414 W. 12TH STREET SUITE 5
TEMPE, ARIZONA 85281
PHONE: 800-858-0519
WEBSITE: WWW.TOTTURF.COM

DETAIL-7
45 DEGREE TURN-DOWN TO LOOSE
FILL MATERIAL

DATE: 09-13-2016
REVISION DATE: 12-12-2016
SCALE: N.T.S.
DRAWN BY: ATL
SIGNED/APPROVED: